Arborist 200 Brute force and high output





Customer category

Contractor • Large Scale Forestry Clearance

Looking for even greater performance than that of a 150 mm machine, the Arborist 200 has to be on your shopping list. Powered by a 45hp Kubota diesel engine with masses of torque, pumping wood waste through a massive 200mm x 280mm letterbox, this is a machine that will impress arborists, tree surgeons and contractors, day-in, day-out. It's heavy-duty construction means it will stand the test of time and maintain a healthy residual value and a strong return on investment

The backbone of the Arborist 200s design is based on a deep beam, high tensile steel chassis which creates tremendous strength and ensures a robust performance. A new, generous in-feed hopper, measuring 1200mm x 840mm, means that free-flow of bulky material can be handled without having to trim to a more manageable size. As the material passes through twin, horizontal, hydraulically powered feed rollers, the patented electronically controlled No-Stress system automatically manages the throughput of material to maximise chipping efficiency.

Arborist 200

Technical Specification...



Key features

• 200mm chipping capacity

• 45hp Kubota turbo diesel engine

• Disc-Blade chipping technology

• Twin, horizontal, hydraulic feed rollers

Bottom-bar Safety Mechanism

LED Lighting

No-Stress power control

● Top control bar

● 1260kg weight











| Capacity | 200mm |
|------------------------|---------------------------|
| Engine Make | Kubota |
| Engine | 45hp |
| Fuel | Diesel |
| Tractor Required | n/a |
| Chipping Flywheel | Disc Blade |
| Flywheel Speed | 1500rpm |
| Blades | 4 |
| Hydraulic Feed Rollers | Twin Horizontal Hydraulic |
| Turntable | n/a |
| Power Control | No-Stress |
| Fuel Capacity (engine) | 27 L |
| Tyre Size (towed) | 175R13C |
| Spare Wheel | Optional |

| Tonnes per hour | 7 |
|-----------------------------|--------------------|
| Infeed Chute Aperture | 1200mm x 840mm |
| Infeed Throat Size | 200mm x 280mm |
| Discharge Chute | 280° Rotation |
| Hydraulic Oil Capacity | 27 L |
| Clutch | Optional |
| Hour Meter | On RDS control box |
| Length (transport) | 3990mm |
| Width (transport) | 1440mm |
| Height | 2695mm |
| Weight | 1260kg |
| Sound Power LWA | 116dB(A) |
| Sound Pressure LPA | 92dB(A) |
| Bottom-bar Safety Mechanism | Standard |