

The Future of Powered Wheelbarrows and Mini Dumpers



BENDI 300

BENDI 450

RIGID 300

# TRUXTA powered BENDI mini dumper

Tufftruk Limited introduce a range of TRUXTA powered mini dumpers that provide maximum versatility and light touch operation, available with battery power, petrol or diesel.

The new BENDI 4x4 mini dumper provides access even in the tightest corners. At just 726mm wide the TRU**XTA** 4x4 is really compact and gets into places other units can't.

A BENDI mini dumper's articulated chassis means the TRUXTA handles corners with the minimum effort - just steer around bends and corners - no need to lift or reposition.

With a massive skip capacity 300kg or 450kg the TRUXTA BENDI mini dumper offers excellent load capacity in and around sites and gardens.

The well balanced robust unit weighs in at just 200kg, easily transportable from site to site, and compact enough to store



### TRUXTA well balanced for ease of use

300 450

In Operation -The key factor is that operators don't have to rely on physical strength or brute force with the BENDI's easy steer handling.

The squeeze & go controls (no mechanical gearboxes) make for the easiest use for any operator, weak or strong. A fail-safe dead-man braking system keeps the operator safe at all times.

Even when tipping the 2 stage self- tip provides optimum balance, with a skip ramp as an option.

**300 BENDI** - 300kg payload, articulated **450 BENDI** - 450kg payload. articulated













- It's the 4x4 patented drive system that gives the TRUXTA range the power for heavy loads. Combine this with a massive 300kg skip capacity and flotation tyres fitted as standard.
- Robust heavy duty construction and a well balanced skip means the TRUXTA is built for all sorts of materials and tough terrains.
- The patented fail-safe dead-man brake system and intuitive hydrostatic controls gives the TRUXTA operator the safest possible operation.
- Easy access to the fuel filler cap and daily check areas for servicing.
- Uniquely available as a battery powered option operators get a quiet environmentally friendly option for the garden or domestic application.





## TRUXTA Hydrostatic Controls

With the TRUXTA petrol and diesel you get a smooth operation with squeeze & go hydrostatic system.

On the electric, the twist-grip throttle control increases your speed, just twist & go.

TRUXTA powered wheel barrows and mini dumpers - built for durability - hydrostatic system - no slipping belts - sealed for life and maintenance free.

The TRU**XTA** - 2 stage self-tipping skip requires no manual lifting. The ultimate **Skip Tip Angle equals** no leftovers, just a **Totally Empty Skip**.















The TRUXTA RIGID powered wheel barrow offers a compact

300 RIGID - 300kg payload

## TRUXTA Accessories

With plenty of attachments the TRUXTA shows its versatility
























All dimensions unless otherwise stated are in millimetres. Dimensions TB300 BENDI (TB450 BENDI)

Turning Circle

#### **Specifications**

|                                 | TB 300 BENDI  |                         |                                |  |
|---------------------------------|---|-------------------------|--------------------------------|--|
| Model                           | Petrol<br>TB 300G   | Diesel<br>TB 300D       | Electric<br>TB 300E            |  |
| Engine/Motor/<br>Power (kW)/hp  | Honda GX 160<br>(3.6) 4.8                                 | Yanmar L48<br>(3.5) 4.7 | DC Brushless Motor<br>800w/24v |  |
| Fuel Type                       | Unleaded<br>Petrol (4 stroke)                             | Diesel                  | 2 x 12v Batteries              |  |
| Fuel Capacity                   | 3.1 litres  | 2.5 litres              |                                |  |
| Max Payload (kg)                | 300   | 300                     | 300                            |  |
| Unladen Weight (kg)             | 170   | 201                     | 224                            |  |
| Working Gradient                | 25°   | 25°                     | 25°                            |  |
| Drive & Controls                | Hydrostatic System  |                         | 24v Motor Gearbox              |  |
| Brake System                    | Fail-safe Dead-man Handle (International patents pending) |                         |                                |  |
| Standard<br>Fitment Tyres       | Flotation with option for turf tyres                      |                         |                                |  |
| Travel Speed<br>Forward/Reverse | 0-4 mph<br>0-1.5 mph                                      |                         | 0-3.5 mph<br>0-1.5 mph         |  |
| Noise Level (db)                | < 94  | < 100                   | < 69                           |  |
| Hand Arm<br>Vibration           | 3.6 m/s²  | 3.8 m/s <sup>2</sup>    | 2.5 m/s <sup>2</sup>           |  |

| A 12 month warranty is applicab | e on all Tufftr <b>uk</b> machines. |
|---------------------------------|-------------------------------------|
|---------------------------------|-------------------------------------|


|                                 | TB 450 BENDI  |                         |                                 |  |
|---------------------------------|---|-------------------------|---------------------------------|--|
| Model                           | Petrol<br>TB 450G   | Diesel<br>TB 450D       | Electric<br>TB 450E             |  |
| Engine/Motor/<br>Power (kW)/hp  | Honda GX 200<br>(3.6) 4.8                                 | Yanmar L48<br>(3.5) 4.7 | DC Brushless Motor<br>1000w/24v |  |
| Fuel Type                       | Unleaded<br>Petrol (4 stroke)                             | Diesel                  | 2 x 12v Batteries               |  |
| Fuel Capacity                   | 3.1 litres  | 2.5 litres              |                                 |  |
| Max Payload (kg)                | 450   | 450                     | 450                             |  |
| Unladen Weight (kg)             | 180   | 219                     | 255                             |  |
| Working Gradient                | 25°   | 25°                     | 25°                             |  |
| Drive & Controls                | Hydrostatic System  |                         | 24v Motor Gearbox               |  |
| Brake System                    | Fail-safe Dead-man Handle (International patents pending) |                         |                                 |  |
| Standard<br>Fitment Tyres       | Flotation with option for turf tyres                      |                         |                                 |  |
| Travel Speed<br>Forward/Reverse | 0-4 mph<br>0-1.5 mph                                      |                         | 0-3.5 mph<br>0-1.5 mph          |  |
| Noise Level                     | < 94  | < 100                   | < 69                            |  |
| Hand Arm<br>Vibration           | 4.6 m/s <sup>2</sup>                                      | 3.8 m/s <sup>2</sup>    | 2.5 m/s <sup>2</sup>            |  |


We reserve the right to change specification without prior notice.











#### **Specifications**

| TR 300 RIGID                    |   |                      |                             |  |  |
|---------------------------------|---|----------------------|-----------------------------|--|--|
| Model                           | Petrol<br>TR 300G   | Diesel<br>TR 300D    | Electric<br>TR 300E         |  |  |
| Engine/Motor Power (kW)/hp      | Honda GX 160 (3.6) 4.8                                    | Yanmar L48 (3.5) 4.7 | DC Brushless Motor 800w/24v |  |  |
| Fuel Type                       | Unleaded Petrol<br>(4stroke)                              | Diesel               | 2 x 12v Batteries           |  |  |
| Fuel Capacity                   | 3.1 litres  | 2.5 litres           |                             |  |  |
| Max Payload (kg)                | 300   | 300                  | 300                         |  |  |
| Unladen Weight (kg)             | 137   | 148                  | 168                         |  |  |
| Working Gradient                | 25°   | 25°                  | 25°                         |  |  |
| Drive & Controls                | Hydrostatic System  |                      | 24v Motor Gearbox           |  |  |
| Brake System                    | Fail-safe Dead-man Handle (International patents pending) |                      | patents pending)            |  |  |
| Standard<br>Fitment Tyres       | Flotation with option for turf tyres                      |                      |                             |  |  |
| Travel Speed<br>Forward/Reverse | 0-4 mph<br>0-1.5 mph                                      |                      | 0-3.5 mph<br>0-1.5 mph      |  |  |
| Noise Level (db)                | < 94  | < 100                | < 69                        |  |  |
| Hand Arm<br>Vibration           | 2.5 m/s <sup>2</sup>                                      | 5.9 m/s²             | 2.5 m/s <sup>2</sup>        |  |  |

A 12 month warranty is applicable on all Tufftruk machines.

All dimensions unless otherwise stated are in millimetres.

We reserve the right to change specification without prior notice.

09/2014

#### For more information

call us direct, or contact:



innovative smart moving equipment

